

Himin Clean Energy Holdings Co.,Ltd  
Himin Solar Energy Group Co.,Ltd

HG-205S  
205W



Monocrystalline photovoltaic module



## MONOCRYSTALLINE SILICON PHOTOVOLTAIC MODULE WITH 200W POWER

Himin Clean Energy Holdings Co.,Ltd has concentrated on solar energy research for 15 years. Himin's HG-205S photovoltaic module is designed for large electrical power requirements, this module has super durability to withstand rigorous operating conditions and is suitable for grid connected systems.

### Features

High-power module(205W)using 125mm square monocrystalline silicon solar cells with 16.1% module conversion efficiency

Photovoltaic module with bypass diode minimizes the power drop caused by shade.Textured cell surface to reduce the reflection of sunlight and BSF(Back Surface Field)structure to improve cell conversion efficiency :18.4%

Using low-iron tempered glass,EVA resin and an aluminium frame for extended outdoor use  
DC 24V system and high-voltage output for grid connected system

Output terminal:Lead wire with waterproof connector

## Specifications

HG-205S

Cell	Monocrystalline silicon solar cells, 125mm square
Number of cells and connections	72 in series
Application	DC 24V system
Maximum system voltage	DC 1,000V
Series fuse rating	10A
Nominal power	205W
Dimensions	1580 808 50mm
Weight	16.2Kg
Type of output terminal	Lead wire with connector

## Absolute maximum ratings

Parameters	Rating	Unit
Operating temperature	-40 to +85	
Storage temperature	-40 to +85	


## Temperature coefficients

$P_m$	-0.490%/
$I_{sc}$	+0.050%/
$V_{oc}$	-152mv/

## Electro-optical characteristics

Parameters	Symbol	Min.	Type	Unit	Conditions
Open circuit voltage	$V_{oc}$	45.7		V	Standard test conditions (STC)
Maximum power voltage	$V_{pm}$	38.3		V	
Short circuit current	$I_{sc}$	5.69		A	Irradiance 1,000W/m <sup>2</sup>
Maximum power current	$I_{pm}$	5.35		A	
Maximum power	$P_m$	194.8	205.0	W	AM1.5
Encapsulated solar cell efficiency	$c$	18.4		%	Module temperature 25
Module efficiency	$m$	16.1		%	


## Characteristics



## Applications

- Grid connected residential system
- Office buildings
- Solar power stations
- Solar villages
- Villas, mountain cottages
- Pumps
- Lighting equipment
- Traffic signs
- Radio relay stations
- Beacons
- Telemeter systems
- Telecommunication systems

## Outline dimensions



In the absence of confirmation by specification sheets, Himin takes no responsibility for any defects that any occur in equipment using any Himin products shown in catalogs, data books, etc. Contact Himin in order to obtain the latest specification sheets, before using any Himin products. Specifications are subject to change without notice.